


Working Height Max. Horizontal Reach Max. Up And over Clearance Max. Overall Lift Capacity Max.

Overall Width and Length

17.8 m (58'5") 9.18 m (30'1") 8.16 m (26'9") 260 kg (573 lb) 2.3 x 7.2 m (7'7" x 23'7")

LA16JE Articulated Boom Lifts-Electric Drive

LA16JE SPECIFICATIONS >>>





DIMENSIONS	
Working Height Max.	17.8 m (58'5")
Platform Height Max.	15.8 m (51'10")
Operating Amplitude Max.	9.78 m (32'1")
Horizontal Reach Max.	9.18 m (30'1")
Up And Over Clearance Max.	8.16 m (26'9")
Platform Size (LxWxH)	1.83 x 0.76 x 1.1 m (6' x 2'6" x 3'7")
A. Length (Stowed/Transport)	7.2 m (23'7")
B. Width (Stowed/Transport)	2.3 m (7'7")
C. Height (Stowed/Transport)	2.35 m (7'9")
D. Ground Clearance	0.37 m (1'3")
E. Wheelbase	2.36 m (7'9")

POWER	
Battery (Lithium)	51.2 V / 304 Ah
Charger	48 V / 60 A
Lifting Motor	AC 10 kW
Drive Motor	AC 3.3 kW
Auxiliary Power Unit	12 V / DC
Hydraulic Tank Capacity	65 L (17gal)

PRODUCTIVITY	
Overall Lift Capacity Max.	260 kg (573 lb)
Platform Occupancy Max.	2
Platform Rotation	± 90°
Jib Length	1.65 m (5'5")
Vertical Jib Rotation (Up/Down)	-70° ~ +72°
Turntable Rotation	360° Discontinuous
Turntable Tailswing	0 m (0')
Drive Speed (Stowed)	5 km/h (3.1 mph)
Drive Speed (Raised)	1 km/h (0.6 mph)
Gradeability	45 %
Tilt Sensor Activation (Side to Side/Front to Back)	X 5° / Y 5°
Turning Radius (Inside/Outside)	2.06 / 4.78 m (6'9" / 15'8")
Tire Size (Solid Off-road)	33 x 12 - 20
Drive Steering Type	4WD x 2WS

LA16JE Working Range							
20m 65'7"							
18m 59'1"							
16m 52'6"				1			
14m 45'11"	\forall						
12m 39'4"				+ + + + + + + + + + + + + + + + + + + 	Blb)		
1 0m 32'10"							
8m 26'3"				11 Ca		4	
6m 19'8"							
4m 13'1"		\rightarrow				,	
2m 6'7"	Da		1				
Om 0'00"			Married				
-2m -6'7"	Om 0'00"	2m 6'7"	4m 13'1"	6m 19'8"	8m 26'3"	10m 32'10"	12m 39'4"

Overall Weight 7.300 kg (16.093 lb)	WEIGHT	
1,220 1.9 (12,020 1.2)	Overall Weight	7,300 kg (16,093 lb)