



Working Height Max. Overall Lift Capacity Max. Overall Width Overall Length Overall Weight 6.5 m (21'4") 240 kg (529 lb) 0.76 m (2'6") 1.39 m (4'7") 895 kg (1,973 lb)

## LS0507EM Electric Scissor Lifts E-Drive

## LS0507EM SPECIFIATIONS >>>







DIMENSIONS	
A. Working Height Max.	6.5 m (21'4")
B. Platform Height Max.	4.5 m (14'9")
C. Platform Height (Stowed)	0.94 m (3'1")
D. Platform Length	1.3 m (4'3")
E. Platform Width	0.72 m (2'4")
F. Extension Deck (Roll Out)	0.6 m (1'11")
G. Overall Length	1.39 m (4'7")
H. Overall Length (Without Ladder)	1.34 m (4'5")
I. Overall Width	0.76 m (2'6")
J. Stowed Height (Rails Up)	2 m (6'7")
K. Stowed Height (Rails Down)	1.64 m (5'5")
L. Wheelbase	1.07m (3'6")
M. Ground Clearance (Pothole Raised)	60 mm (2.3")
N. Ground Clearance (Pothole Deployed)	20 mm (0.79")

PRODUCTIVITY	
Overall Lift Capacity Max.	240 kg (529 lb)
Extension Deck Capacity	110 kg (242 lb)
Platform Occupancy Max. (Indoor/Outdoor)	2/1
Drive Speed (Stowed)	1.5 km/h (0.9 mph)
Drive Speed (Raised)	0.3 km/h (0.2 mph)
Turning Radius (Inside/Outside)	0.25 / 1.6 m (10" / 5'3")
Lift/Lower Time	23 / 21 s
Gradeability	25 %
Tilt Sensor Activation (Side to Side/Front to Back)	X 1.5°/ Y 3°
Tire Size (Solid Non-marking)	255 x 76 mm (10" x 3")

POWER	
Battery	24 V / 100 Ah
Lithium Battery (Optional)	24 V / 105 Ah
Charger	24 V / 15 A
Lifting Motor	24 V / 1.3 kW
Drive Motor	24 V / 0.45 kW
Hydraulic System Volume	4.5 L (1 gal 2 pt)
Hydraulic Tank Capacity	5 L (1 gal 3 pt)

895 kg (1,973 lb)